



attachment to interview summary - /tgs/ 1774
19 OCT 2010

Fax Cover Sheet



NY Address:
875 Third Avenue, 8th Floor
New York, NY 10022
P: (212) 808-0700
F: (212) 808-0844

www.nmmlaw.com
E: info@nmmlaw.com

DATE: October 18, 2010

TO:	COMPANY	FAX#	PHONE#
Examiner Tony G. Soohoo	USPTO	571-273-1147	571-272-1147

FROM: Brian C. Anscomb

CLIENT/MATTER: USSN: 10/535,262 **PAGES INCLUDING THIS PAGE:** 2

Dear Examiner Soohoo,

proposed new claim 31 is enclosed for your review and discussion during our October 19, 2010 telephonic interview at 4:00 PM EST. I look forward to discussing this patent application with you tomorrow.

Best regards,

A handwritten signature in dark ink, appearing to read 'Brian C. Anscomb', is written over a light blue horizontal line.

Brian C. Anscomb (Reg. No. 48,641)

The original document will be sent via:

Fax Only: ☒ Yes ☐ No
Email: ☐ Yes ☐ No
Overnight Mail: ☐ Yes ☐ No

Ordinary Mail: ☐ Yes ☐ No
Messenger: ☐ Yes ☐ No
Courier: ☐ Yes ☐ No

THE INFORMATION CONTAINED IN THIS FACSIMILE MESSAGE IS PRIVILEGED AND CONFIDENTIAL INFORMATION INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPYING OF THIS COMMUNICATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE IMMEDIATELY NOTIFY US BY TELEPHONE AND RETURN THE ORIGINAL MESSAGE TO US AT THE ABOVE ADDRESS VIA THE U.S. POSTAL SERVICE. THANK YOU.

If the transmission is not complete, please call (917) 369-8878 and ask for Brian Anscomb

attachment to interview summary- /tgs/ 1774
19 OCT 2010

PROPOSED CLAIM AMENDMENT

DRAFT

31. (new) A static lamination micro-mixer for mixing, dispersing, emulsifying or suspending at least first and second fluid phases, the micro-mixer comprising:
a lower housing part having a first feed channel for the first fluid phase and a second feed channel for the second fluid phase, wherein the first and second feed channels have partially openings on an upper side of the lower housing part;

DRAFT

at least one slotted plate resting on the lower housing part and having first slot openings and second slot openings, wherein the first and second slot openings completely penetrate the slotted plate and are arranged in pairs;

an aperture plate resting on the slotted plate and having at least one slot-shaped aperture opening, wherein the at least one aperture opening completely penetrates the aperture plate; and

DRAFT

a mixing chamber located above the aperture plate,
wherein one end of the first slot openings of each pair is in direct fluidic contact with the first feed channel in the lower housing part and one end of the second slot openings of each pair is in direct fluidic contact with the second feed channel in the lower housing part, wherein the first and second slot openings overlap the aperture opening in the aperture plate,

wherein an overlap between the partial openings on the upper side of the lower housing part, the first and second slot openings in the slotted plate and the aperture opening in the aperture plate is nonidentical in a vertical projection onto the slotted plate, such that

a first continuous, at least twice deflected, fluid pathway is formed from the first feed channel in the lower housing part, through the first slot openings of each pair in the slotted plate, to the mixing chamber located above the aperture plate, and

a second continuous, at least twice deflected, fluid pathway is formed from the second feed channel in the lower housing part, through the second slot openings of each pair in the slotted plate, to the mixing chamber located above the aperture plate

DRAFT